

# CLASS 5 – INFORMATION PROCESSING SYSTEMS

## (Federal Specification AA-C-2786)

Class 5 information processing systems cabinets are GSA-approved for the protection of computing and communication devices for on-line operation of classified systems, including the safeguarding of electronic media and communication devices. Protection for 30 man-minutes against covert entry, 20 man-hours against surreptitious entry, and 10 man-minutes against forced entry

*Style 1 lock – Kaba Mas X-10*

*Style 2 lock – S&G 2740B*

*Style 1 and 2 locks are in accordance with Federal Specification FF-L-2740*

### 19" Rack Mount, 13u Equipment Capacity (Size I)

Fan Ventilation (CFM per fan) Minimum – 105 CFM

Max Outside Dimensions – 34"H x 26"W x 46"D

*Approx. Shipping Weight: 1080 lbs; Cube:33.3*

**7110-01-707-7647** Gray, Style 1 lock

**7110-01-707-7649** Gray, Style 2 lock

*Accessories available upon request*



### 19" Rack Mount, 26u Equipment Capacity (Size II)

Fan Ventilation (CFM per fan) Minimum – 230 CFM

Max Outside Dimensions – 56"H x 26"W x 46"D

*Approx. Shipping Weight: 1590 lbs; Cube:45.83*

**7110-01-707-7653** Gray, Style 1 lock

**7110-01-707-7651** Gray, Style 2 lock

*Accessories available upon request*



### **23” Rack Mount, 13u Equipment Capacity (Size III)**

Fan Ventilation (CFM per fan) Minimum – 230 CFM

Max Outside Dimensions – 34”H x 32”W x 46”D

*Approx. Shipping Weight: 1200 lbs; Cube 33.3*

**7110-01-707-7646** Gray, Style 1 lock

**7110-01-707-7652** Gray, Style 2 lock

*Accessories available upon request*



### **23” Rack Mount, 26u Equipment Capacity (Size IV)**

Fan Ventilation (CFM per fan) Minimum – 400 CFM

Max Outside Dimensions – 56”H x 32”W x 46”D

*Approx. Shipping Weight: 1680 lbs; Cube: 50*

**7110-01-707-7648** Gray, Style 1 lock

**7110-01-707-7650** Gray, Style 2 lock

*Accessories available upon request*



### **Combination Locks**

#### **SINGLE LOCK DESIGN**

**Style 1 – Basic self-contained**

**Style 2 – Interoperable/Networked**

**5340-01-613-2078**, Style 1, Kaba Mas X-10

**5340-01-613-2080**, Style 2, S&G 2740B